EAST Search History

Ref #	Hits	Search Query	DBs	Default Operator	Plurals	Time Stamp
L1	20	high near3 resolution with two adj4 (phase) near5 two	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2007/07/17 08:36
L2	216	high near3 resolution with two adj4 (phase)	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2007/07/17 08:48
L3	27	high near3 resolution with two adj4 (phase) and (ccd or cmos)	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2007/07/17 08:56
L4	71	high near3 resolution with two adj4 (phase) and (ccd or cmos or sensor)	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2007/07/17 09:06
L5	464	257/246-248.ccls.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2007/07/17 09:06
L6	0	257/246-248.ccls. and highn near4 resolution	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2007/07/17 09:07
L7	31	257/246-248.ccls. and high near4 resolution	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2007/07/17 09:07

EAST Search History

L10	46	(chang\$4 or select\$4) with mode with high with low with resolution and shift adj register	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2007/07/17 11:43
L11	37	(chang\$4 or select\$4) with mode with high with low with resolution and shift adj register and (clock or phase)	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2007/07/17 11:44
L12	28	(chang\$4 or select\$4) with mode with high with low with resolution and shift adj register and (clock or phase)and gate	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2007/07/17 11:50
L13	53	high with low with resolution with phase and shift adj register	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2007/07/17 11:51



Home | Login | Logout | Access Information | Alerts |

Welcome United States Patent and Trademark Office

☐ Search Results

BROWSE

SEARCH

IEEE XPLORE GUIDE

Results for "((((((phase)<in>metadata)))<and>(high <near> resolution<in>metadata)))<and..."
Your search matched 3 of 2178 documents.

⊠e-mail

A maximum of 100 results are displayed, 25 to a page, sorted by Relevance in Descending order.

» Search Options

View Session History

New Search

» Key

IEEE JNL

IEEE Journal or Magazine

nagaziile

IET JNL

IET Journal or Magazine

IEEE CNF

IEEE Conference Proceeding

IET Conference

IET CNF

Proceeding

IEEE STD IEEE Standard

Modify Search

((((((phase)<in>metadata))<and>(high <near> resolution<in>metadata)))<and>(shift <

Search

Check to search only within this results set

Display Format:

 Cita

Citation C Citation & Abstract

view selected items

Select All Deselect All

1. A 1/3-in 510(H)×492(V) CCD image sensor with mirror image function

Hojo, J.; Naito, Y.; Mori, H.; Foujikawa, K.; Kato, N.; Wakayama, T.; Komatsu,

Electron Devices, IEEE Transactions on

Volume 38, Issue 5, May 1991 Page(s):954 - 959

Digital Object Identifier 10.1109/16.78364

AbstractPlus | Full Text: PDF(444 KB) | IEEE JNL

Rights and Permissions

2. A distributed BIST technique for diagnosis of MCM interconnections

Pendurkar, R.; Chatterjee, A.; Zorian, Y.;

Test Conference, 1998. Proceedings. International

18-23 Oct. 1998 Page(s):214 - 221

Digital Object Identifier 10.1109/TEST.1998.743154

AbstractPlus | Full Text: PDF(540 KB) | IEEE CNF

Rights and Permissions

3. Dynamic focussing and ultrasonic imaging

Martin, M.; Piquard, J.;

Acoustics, Speech, and Signal Processing, IEEE International Conference on I

Volume 7, May 1982 Page(s):1513 - 1515

AbstractPlus | Full Text: PDF(44 KB) | IEEE CNF

Rights and Permissions

Help Contact Us Privacy &

© Copyright 2006 IEEE --

indexed by Inspec°